



# ABA Mini Standard S10(W1) and Stainless S40(W4)



S10



S40



ABA Mini features rolled-up band edges that are gentle on hoses. The band tongue that fits under the hose is profiled for added strength. The nut is retained even if the screw is removed. Furthermore the screw has a hexagonal head and can be tightened with a flexible socket wrench. The ABA Mini is particularly suitable for use on small, thin-walled hoses. This little clamp provides an excellent clamping force well over screwless clamps.

**ABA Mini Standard-S10(W1):** Electro zinc plated.

**ABA Mini Stainless-S40(W4):** All parts are made of SS 2333/AISI 304 stainless steel.

Standard – S10			
Hose size	Minimum Ø	Supplied Ø	Rec. tightening torque Nm
Mini 7	6,5	7,5	1,5
Mini 8	7	8,5	
Mini 9	8	9,5	
Mini 10	9	10,5	
Mini 11	9,5	11,5	
Mini 12	10,5	12,5	
Mini 13	11,5	13,5	
Mini 14	12,5	14,5	
Mini 15	13,5	15,5	
Mini 16	14	16,5	
Mini 17	15	17,5	

Stainless – S40			
Hose size	Minimum Ø	Supplied Ø	Rec. tightening torque Nm
Mini 8	7,5	8,5	1,5
Mini 9	8,5	9,5	
Mini 10	9,5	11	
Mini 11	10,5	12	
Mini 12	11,5	13	
Mini 13	12,5	14	
Mini 14	13,5	15	
Mini 15	14,5	16	
Mini 16	15	17	
Mini 17	16	18	